


Date of Preparation: January 1, 2016

Use in case of an emergency only (613) 996-6666

SECTION I - PRODUCT AND PREPARATION INFORMATION								33C48
 SCHWARTZ ADVANCED CHEMISTRY SOLUTIONS	777 McKay Road Pickering, Ontario L1W 3A3 (905)683-0411			TRADE NAME: GLOSS METAL BASE TOPCOAT RFU MANUFAC. CODE: 33C48 PRODUCT CLASS: PAINT RELATED UN1263 - 3.3 WHIMIS CLASS: B, D-2		Prepared by: Technical Committee		
	SECTION II - HAZARDOUS INGREDIENTS							
INGREDIENT	CAS NO.	%	NATURE OF HEALTH HAZARD AND ROUTE OF ENTRY	TYPE OF HAZARD	EXPOSURE LIMIT	SOURCE	OTHER HAZARDS	
PETROLEUM SOLVENT	8032-32-4	3 - 7	HARMFUL IF INHALED, IRRITANT SKIN CONTACT	ACUTE	300 PPM	TLV	CARCINOGEN SUSPECT ANEMIA	
ETHYL BENZENE	100-41-4	1 - 5	HARMFUL IF INHALED, IRRITANT SKIN CONTACT	ACUTE	100 PPM	TLV		
FORMALDEHYDE	50-00-0	.1 - 1	HARMFUL IF INHALED, IRRITANT SKIN CONTACT	CHRONIC				
BUTANOL	71-36-3	5 - 10	HARMFUL IF INHALED, IRRITANT SKIN CONTACT	CHRONIC	50 PPM	TLV		
PETROLEUM SOLVENT	8052 41 3	< .1	HARMFUL IF INHALED, IRRITANT SKIN CONTACT CAUSES IRRITATION	ACUTE				
TOLUOL	108-88-3	10-30	HARMFUL IF INHALED, IRRITANT SKIN CONTACT	ACUTE	100 PPM	TLV		
XYLENE	1330-20-7	40-70	HARMFUL IF INHALED, IRRITANT SKIN CONTACT	ACUTE	100 PPM	TLV		
AROMATIC HYDROCARBON	64742-95-6	10-30	HARMFUL IF INHALED, IRRITANT SKIN CONTACT	ACUTE	50 PPM	TLV		
PETROLEUM NAPHTHA, HEAVY AROMATIC	647-42-94-5	1 - 5	HARMFUL IF INHALED, IRRITANT SKIN CONTACT	ACUTE	500 PPM	OSHA-PEL		
NON-HAZARDOUS		15-40						
SECTION III - PHYSICAL DATA								
ODOUR AND APPEARANCE	PH VALUE	PERCENT VOLATILE BY VOLUME		EVAPORATION RATE				
AROMATIC		76%		GREATER THAN BUTYL ACETATE				
CLEAR								
BOILING POINT		FREEZING POINT		SPECIFIC GRAVITY				
93 °C		°C		0.92				
SECTION IV - FIRE AND EXPLOSION HAZARDS								
FLAMMABILITY CLASSIFICATION /	FLASHPOINT	HAZARDOUS COMBUSTION PRODUCTS						
Class 3, Division 3	6 °C	CARBON DIOXIDE, CARBON MONOXIDE						
	TAG CUP	EXTINGUISHING MEDIA						
		Foam, dry chemical, carbon dioxide or any class B extinguishing agent						
UNUSUAL FIRE AND EXPLOSION HAZARDS								
Vapours may ignite explosively. Vapours may spread long distances. Prevent build-up of vapours. Extinguish all pilot lights and turn off heaters, non-explosion-proof electrical equipment and all other sources of ignition. Keep away from and do not store or use near heat, sparks or flames caused by such sources as electricity, static discharge, welding, grinding or flamecutting operation. Ground all equipment. Use spark-proof tools and conductive shoes to avoid sparking hazards.								
SPECIAL FIREFIGHTING PROCEDURES								
Exposure to vapours or products of combustion should be avoided. Self-contained breathing apparatus is recommended. Vapours may form an explosive mixture with air. Closed containers may rupture when exposed to extreme heat.								
SECTION V - HEALTH HAZARD DATA: TOXICOLOGICAL PROPERTIES AND FIRST AID MEASURES								
ACUTE EFFECTS OF OVEREXPOSURE				EMERGENCY AND FIRST AID PROCEDUES				
INHALATION:	Excessive exposure to vapours or spray mists can result in headache, dizziness, incoordination and loss of consciousness. Irritation of the eyes, nose, throat and lungs can also occur when exposed to high vapour concentrations. Some reports have associated repeated and prolonged occupational overexposure to solvents with permanent nervous system damage.			INHALATION:	Remove victim to fresh air. Restore breathing. Treat symptomatically. Consult a physician.			
EYE CONTACT:	This material can cause eye irritation. The effects are usually reversible.			SPLASH (EYES):	Flush immediately with large amounts of water for at least 15 minutes. Take to a physician for medical treatment.			
SKIN CONTACT:	This material may cause defatting and irritation of skin (Dermatitis) upon prolonged or repeated contact.			SPLASH (SKIN):	Wash affected areas with soap and water. Remove contaminated clothing.			
INGESTION:	Swallowing can cause nausea, vomiting, diarrhea and loss of consciousness.			INGESTION:	Drink 1 or 2 glasses of water to dilute. DO NOT INDUCE VOMITING. Consult a physician or Poison Control center immediately. Treat symptomatically.			
CHRONIC EFFECTS OF OVEREXPOSURE				IRRITANT		SENSITIZER		
n/av				YES: Skin and Eye		YES: Skin		

Date of Preparation: January 1, 2016

Use in case of an emergency only (613) 996-6666

SECTION VI - REACTIVITY DATA		33C48
STABILITY:		HAZARDOUS POLYMERIZATIONS:
Stable		Will not occur
INCOMPATIBILITY: (Materials to avoid)		CONDITIONS TO AVOID:
Oxidizing compounds		Vapour concentrations
HAZARDOUS DECOMPOSITION PRODUCTS:		Ignition sources
None known		
SECTION VII - SPILL OR LEAK PROCEDURES		
STEPS TO BE TAKEN in case material is Released or Spilled		WASTE DISPOSAL METHOD
Restrict access to area. Remove all sources of ignition. Ventilate area. Absorb spill with an absorbent material such as vermiculite or sand and place material into a closed container. If a large spill, dike area to prevent this material from entering water systems or sewers. Wear protective equipment during cleanup.		Dispose of this material in accordance with Federal, Provincial, and Municipal regulations.
SECTION VIII - SPECIAL PROTECTION INFORMATION		
PERSONAL PROTECTION EQUIPMENT		
PROTECTIVE GLOVES:		EYE PROTECTION:
Chemical resistant gloves made of Viton should be used. Gloves made of nitrile, neoprene or rubber may be used for exposure of short duration.		Chemical safety goggles should be worn to prevent eye contact. A face shield may also be necessary.
RESPIRATORY PROTECTION:		OTHER PROTECTIVE EQUIPMENT:
An organic vapour cartridge respiratory mask shall be worn to prevent the inhalation of vapours or spray mist when the TLB or PEL is exceeded. If respiratory protection is required, institute a complete respiratory protection program. Refer to the CSA Standard Z94.4 M1982 "Selection, Care and Use of Respirators" available from the Canadian Standard Association, Rexdale, Ontario. M9W 1R3		Eye wash fountain and safety showers must be available in areas where this material is used. Wear protective clothing to prevent skin contact.
		ENGINEERING CONTROLS - VENTILATION:
		General (dilution) ventilation is required during normal use. Local exhaust ventilation may be required during certain operations to keep exposure level below the limit listed in Section II of this data sheet.
SECTION IX - SPECIAL PRECAUTIONS		
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING		OTHER PRECAUTIONS
<p>STORAGE: Keep storage area separate from populated work areas. Store in a cool, dry, well ventilated area, out of direct sunlight and away from incompatible materials and any source of ignition. Ventilation fans and electrical equipment should be non-sparking.</p> <p>HANDLING: Avoid prolonged or repeated inhalation of vapours or spray mist. Avoid prolonged or repeated skin contact. Ground and bond equipment and container to prevent a static charge build-up.</p> <p>ATTENTION: Emptied containers may retain hazardous residue and explosive vapours. Keep away from heat, sparks and flames. Do not cut puncture or weld near this container. Follow label warning until container is thoroughly cleaned or destroyed.</p>		