



Water and Solvent-Based Wood Floor Sealers

The Schwartz Water-based and Solvent based Wood Floor Sealers are formulated for use with Schwartz Chemical Premium Polyurethane floor finishes. Most flooring professionals reach for these products because of their low VOC, high build and low odour formulae. Others use Schwartz Wood Floor Sealers because of their quick drying and short recoat time, or the way both the solvent and water-based grades minimize side-bonding and grain-raising. When you seek a VOC Compliant, Wood Floor Sealer designed for use with Schwartz Chemical Premium Polyurethane Floor Finishes, choose Schwartz Wood Floor Sealers.



SCHWARTZ

ADVANCED CHEMISTRY SOLUTIONS

www.schwartzchem.com



Water and Solvent-Based Wood Floor Sealers

Flooring professionals who prefer a low-VOC, low-odour sealer with superior tannin- and stain-blocking properties should consider these products. A tie coat for use on bare floor under Schwartz Chemical Premium Polyurethane Floor Finishes and a compatible base for use with most competitive top coats, Schwartz Wood Floor Sealers are an excellent choice for all of your hardwood floor finishings.

FEATURES

- Low VOC <45 g/L & maximum 350g/L grades
- Available in water-based and solvent-based technologies
- Low odour water-based formula
- Quick drying properties
- Schwartz Sealers offer superior tannin and stain blocking properties
- Minimize grain raising
- High solids and high build

SUMMARY OF HOW TO USE THIS PRODUCT*

Follow the manufacturer's recommended surface preparation guidelines, and use an applicator appropriate for the sealer and technology being used.

Apply one coat for most wood surfaces. Two coats may be required for wood high in tannin when using the Water-based sealer. Let the Schwartz Wood Floor Sealer cure as recommended before recoating. The Schwartz Water-based sealer may not need to be abraded between coats. Contact Schwartz or consult the product data sheet for more detailed instructions.

* For detailed instructions, please see the product data sheet.

ORDERING INFORMATION

Code	Name	Containers
1C259	Low VOC Clear Floor Sealer	18.9L (5 U.S. Gallon pail)
1C360	Low VOC Sanding Sealer	18.9L (5 U.S. Gallon pail)
81C1	H2O Waterborne Sealer	3.78L / 18.9L (5 U.S. Gallon pail)

HOW TO ORDER

Order this product today by calling (905) 683-0411 or toll-free 1-866-519-9674. Our sales staff will be pleased to provide any additional information you may require, including the product data sheet. We would also be pleased to discuss delivery options.

ABOUT SCHWARTZ CHEMICAL CORPORATION

Schwartz Chemical Corporation operates a 38,000 sq. ft. Class 1 Division 1 facility in Pickering, Ontario, where it formulates, manufactures and packages solvent-based, water-based and UV/radiation cure, bake and air dry coatings and adhesives for a wide range of applications.

Our products include floor finishes, plumbing solvent cements, primers and cleaners, adhesives, millwork, furniture and cabinetry finishes, and metal and specialty coatings.

Schwartz Chemical Corporation
777 McKay Road
Pickering, ON L1W 3A3
Tel: (905) 683-0411
Toll-free: 1-866-519-9674
FAX (905) 428-2057
www.schwartzchem.com

© 2012 Schwartz Chemical Corporation This brochure is summary in nature and subject to change without notice.

