



## H2O Premium Wood Floor Finishes

Schwartz H2O Premium Wood Floor Finish is a high- solids polyurethane water-based topcoat. This single component, low VOC, low odour formula is the flooring professionals' choice because it's easy to apply and dries hard for a durable finish suitable for all interior hardwood floors.

It's outstanding abrasion and chemical resistance to most common household cleaners, makes Schwartz H2O Premium Wood Floor Finish the ideal choice for high traffic areas.



**SCHWARTZ**

ADVANCED CHEMISTRY SOLUTIONS

[www.schwartzchem.com](http://www.schwartzchem.com)



## H2O Premium Wood Floor Finishes

This high-viscosity, H2O wood floor finish suits projects needing high abrasion resistance. It goes on like traditional finishes, levels well, and dries quickly. An ideal choice for apartments, condos, stores, heritage buildings, gymnasiums and other commercial floors.

### FEATURES

- Formulated for high-traffic wood flooring
- Low VOC (180 g/L), to meet regulations
- Low-odour formula
- No need for mixing, straining or in-field chemistry
- No need for new or additional tools
- Goes on like traditional products, without foaming
- Levels well
- High build for each coat, for better coverage
- Quick drying for faster job turnaround
- Impressive gloss

### ABOUT SCHWARTZ CHEMICAL CORPORATION

Schwartz Chemical Corporation operates a 38,000 sq. ft. Class 1 Division 1 facility in Pickering, Ontario, where it formulates, manufactures and packages solvent-based, water-based and UV/radiation cure, bake and air dry coatings and adhesives for a wide range of applications.

Our products include floor finishes, plumbing solvent cements, primers and cleaners, adhesives, millwork, furniture and cabinetry finishes, and metal and specialty coatings.

Schwartz Chemical Corporation  
777 McKay Road  
Pickering, ON L1W 3A3  
Tel: (905) 683-0411  
Toll-free: 1-866-519-9674  
FAX (905) 428-2057  
www.schwartzchem.com

© 2012 Schwartz Chemical Corporation This brochure is summary in nature and subject to change without notice.



### SUMMARY OF HOW TO USE THIS PRODUCT\*

Follow the manufacturer's recommended surface preparation guidelines, and then apply two coats, leaving two to four hours drying time between them. Sand and remove surface dust before applying the second coat. Let the final coat dry well before use. Full cure takes seven days.

\* For detailed instructions, please see the product data sheet.

### ORDERING INFORMATION

Code	Name	Containers
81C90*	H2O Premium Gloss	3.78L / 18.9L (5 U.S. Gallon pail)
81C50	H2O Premium Semi Gloss	3.78L / 18.9L (5 U.S. Gallon pail)
81C30	H2O Premium Satin	3.78L / 18.9L (5 U.S. Gallon pail)

\* Schwartz Chemical recommends using 81C90 for gymnasium floor applications

### HOW TO ORDER

Order this product today by calling (905) 683-0411 or toll-free 1-866-519-9674. Our sales staff will be pleased to provide any additional information you may require, including the product data sheet. We would also be pleased to discuss delivery options.